

## **Table of Contents**

Chapter 1 What is TCPDAQ ActiveX Control? .....	2
1.1 Home Page .....	2
Chapter 2 Module monitoring page.....	4
2.1 EDAM-9015 monitoring page.....	4
2.2 EDAM-9017 monitoring page.....	5
2.3 EDAM-9019 monitoring page.....	6
2.4 EDAM-9050 monitoring page.....	7
2.5 EDAM-9051 monitoring page.....	8
2.6 EDAM-9052 monitoring page.....	9

## Chapter 1 What is TCPDAQ Web Server?

EDAM-9000 I/O modules all features built-in web server. Remote computer or devices can monitor and control I/O status on EDAM-9000 modules remotely through web browser. There is default built-in web page on EDAM-9000 modules.

To use your computer to browse the web page on EDAM-9000 module, you can simply type the IP address to connect to your EDAM-9000 module in web browser. There will be one dialog window asking you to enter the password. After you have typed the correct password, you can start to monitor or control I/O on EDAM-9000 modules.

Notice: Please use Windows Internet Explorer 5.5 (IE 5.5 or later version)

### 1.1 Home Page

- Type the **IP address** in the web browser (example: http://192.168.0.51)
- The home page will pop-up in the browser window to ask you to enter the password



## EDAM-9000 Web Server User's manual

---

- ◆ Enter the correct password and click send button to verify the password. If the password is not correct, a warming message box will show up to remain you to reenter the password

◆



- ◆ If the password is correct, the module monitoring page will pop up in the web browser.

## Chapter 2 Module monitoring page

### 2.1 EDAM-9015 monitoring page

RTD Temperature Input				
Channel	Hi-Alarm	Lo-Alarm	Temperature	RTD Type
AI 0			-050.00C	IEC Pt100 -50~150C
AI 1			Burn out	IEC Pt100 0~400C
AI 2			Burn out	IEC Pt100 -50~150C
AI 3			Burn out	IEC Pt100 -50~150C
AI 4			Burn out	IEC Pt100 -50~150C
AI 5			Burn out	IEC Pt100 -50~150C
AI 6			Burn out	IEC Pt100 -50~150C
Average				Disabled
: No Alarm		: Alarm	Update Time Interval:	1000 msec <input type="button" value="Set"/>

Channel : Channel number of RTD input

Hi-Alarm : Analog channel High alarm status

Lo-Alarm : Analog channel low alarm status

Temperature: Temperature value of RTD input channel

RTD type : RTD type of input channel

Average : Average value of channels which functions in average

Time interval: I/O status update time interval

## 2.2 EDAM-9017 monitoring page

**InLog** EDAM-9017 Voltage Acquisition Web (v1.1)

Running:

Temperature Input				Digital Output			
Channel	Hi-Alarm	Lo-Alarm	Voltage	Input Range	Channel	Status	DO Setting
AI 0			-00.014 V	+/- 10V	DO 0		
AI 1			-00.014 V	+/- 10V	DO 1		
AI 2			-00.014 V	+/- 10V			
AI 3			-00.014 V	+/- 10V			
AI 4			-00.014 V	+/- 10V			
AI 5			-00.014 V	+/- 10V			
AI 6			-00.013 V	+/- 10V			
AI 7			-00.014 V	+/- 10V			
Average				Disabled			
: No Alarm     : Alarm					Update Time Interval: 1000 msec <input type="button" value="Set"/>		

Channel : Channel number of analog input or digital output

Hi-Alarm : Analog channel High alarm status

Lo-Alarm : Analog channel low alarm status

Voltage : Voltage value of analog input channel

Input Range: Range of analog input channel

Status : Digital output status

DO Setting: Set digital output on or off

Time interval: I/O status update time interval

## 2.3 EDAM-9019 monitoring page

InLog EDAM-9019 Temperature Acquisition Web (v1.1)							
Temperature Input					Digital Output		
Channel	Hi-Alarm	Lo-Alarm	Temperature	T/C Type	Channel	Status	DO Setting
AI 0				Burn out	Type J 0~760C	DO 0	
AI 1				Burn out	Type J 0~760C	DO 1	
AI 2				Burn out	Type J 0~760C		
AI 3				Burn out	Type J 0~760C		
AI 4				+0028.67C	Type J 0~760C		
AI 5				Burn out	Type J 0~760C		
AI 6				Burn out	Type J 0~760C		
AI 7				Burn out	Type J 0~760C		
Average				Disabled		:OFF  ON	
Cold junction	+00027.2C		: No Alarm  : Alarm	Update Time Interval: <input type="text" value="1000"/> msec <input type="button" value="Set"/>			

Channel : Channel number of analog input or digital output

Hi-Alarm : Analog channel High alarm status

Lo-Alarm : Analog channel low alarm status

Temperature: Temperature value of T/C input channel

T/C type : Thermal Couple type of input channel

Cold junction: Temperature of T/C cold junction

Average : Average value of channels which functions in average

Status : Digital output status

DO Setting: Set digital output on or off

Time interval: I/O status update time interval

## 2.4 EDAM-9050 monitoring page

**InLog** EDAM-9050 Data Acquisition Web (v1.1)

Receiving:

Digital Input				Digital Output		
Channel	Status	Counts/Latch	Mode	Channel	Status	DO Setting
DI 0	<input checked="" type="radio"/>		Direct input	DO 0	<input type="radio"/>	<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 1	<input checked="" type="radio"/>		Direct input	DO 1	<input type="radio"/>	<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 2	<input checked="" type="radio"/>		Direct input	DO 2	<input type="radio"/>	<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 3	<input checked="" type="radio"/>		Direct input	DO 3	<input type="radio"/>	<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 4	<input checked="" type="radio"/>		Direct input	DO 4	<input type="radio"/>	<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 5	<input checked="" type="radio"/>		Direct input	DO 5	<input type="radio"/>	<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 6	<input checked="" type="radio"/>		Direct input			
DI 7	<input checked="" type="radio"/>		Direct input			
DI 8	<input checked="" type="radio"/>		Direct input			
DI 9	<input checked="" type="radio"/>		Direct input			
DI 10	<input checked="" type="radio"/>		Direct input			
DI 11	<input checked="" type="radio"/>		Direct input			
				<input type="radio"/> OFF <input checked="" type="radio"/> ON		
				Update Time Interval: <input type="text" value="1000"/> msec <input type="button" value="Set"/>		

Channel : Channel number of digital input or output

Status : Current input or output status

Count/Latch: Counter value or latch status of digital input which functions at “Counter” mode or “Latch” mode

Mode : Channel operating mode

DO Setting: Set digital output on or off

Time interval: I/O status update time interval

## 2.5 EDAM-9051 monitoring page

**InLog** EDAM-9051 Data Acquisition Web (v1.1)

Running:

Digital Input				Digital Output		
Channel	Status	Counts/Latch	Mode	Channel	Status	DO Setting
DI 0		<input type="text"/>	Direct input	DO 0		<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 1		<input type="text"/>	Direct input	DO 1		<input type="button" value="ON"/> <input type="button" value="OFF"/>
DI 2		<input type="text"/>	Direct input			
DI 3		<input type="text"/>	Direct input			
DI 4		<input type="text"/>	Direct input			
DI 5		<input type="text"/>	Direct input			
DI 6		<input type="text"/>	Direct input			
DI 7		<input type="text"/>	Direct input			
DI 8		<input type="text"/>	Direct input			
DI 9		<input type="text"/>	Direct input			
DI 10		<input type="text"/>	Direct input			
DI11		<input type="text"/>	Direct input			
COUNTER 0		<input type="text" value="0"/>	Counter Input			
COUNTER 1		<input type="text" value="0"/>	Counter Input			
				<input type="button" value="OFF"/> <input type="button" value="ON"/> Update Time Interval: <input type="text" value="1000"/> msec <input type="button" value="Set"/>		

Channel : Channel number of digital input or output

Status : Current input or output status

Count/Latch: Counter value or latch status of digital input which functions at "Counter" mode or "Latch" mode

Mode : Channel operating mode

DO Setting: Set digital output on or off

Time interval: I/O status update time interval

## 2.6 EDAM-9052 monitoring page

Digital Input				Digital Output			
Channel	Status	Counts/Latch	Mode	Channel	Status	DO Setting	
DI 0			Direct input	DO 0			OFF
DI 1			Direct input	DO 1			OFF
DI 2			Direct input	DO 2			OFF
DI 3			Direct input	DO 3			OFF
DI 4			Direct input	DO 4			OFF
DI 5			Direct input	DO 5			OFF
DI 6			Direct input	DO 6			OFF
DI 7			Direct input	DO 7			OFF
OFF       ON				Update Time Interval: <input type="text" value="1000"/> msec <input type="button" value="Set"/>			

Channel : Channel number of digital input or output

Status : Current input or output status

Count/Latch: Counter value or latch status of digital input which functions at "Counter" mode or "Latch" mode

Mode : Channel operating mode

DO Setting: Set digital output on or off

Time interval: I/O status update time interval